ACCESSORIES

DTM-CONNECT - ACOUSTIC STRAND TENSION METER

DTM-connect is the acoustic tension meter used for quick and easy measurement of the belt tension, also called strand tension, belt strand force or belt tension force.

Optimal belt tension is necessary to ensure a long service life of the belt and a trouble-free operation of your drive.

The device is fully electronic and equipped with the latest microprocessor technology for simple, high-precision measurements.

It is suitable for all belt types, e.g. V-belts, toothed and power belts or ribbed belts, which are in the measuring frequency range between 10 and 600 Hz. The type, colour and quality of the belt have no influence on the measurement result.

DTMCONNECT: SCOPE OF DELIVERY AND DEVICE DESCRIPTION

- Small sensor head
- Flexible gooseneck
- Stable hard case
- OLED display
- On/Off button
- 3 function keys for menu control
- Connection for charging cable
- USB-C charging cable
- Europlug

DTM-CONNECT - FEATURES:

- Non-contact, acoustic measurement technology with a highly sensitive sensor for exact
- belt tension measurement
- Suitable for all belt and tension member types
- Small sensor head on a flexible gooseneck for measurements even in areas difficult to access
- Ergonomic shape for optimal one-hand use
- Integrated, rechargeable lithium polymer battery
- Additional functions via the use of a custom app

MEGADYNE BELTS MEASURING GAUGE

Measurement range from 500mm to 2500mm internal length (Li).
Megadyne belts measuring gauge can be easily mounted on the wall.

forniture per l'industria gelmini s.r.l.
www.forniturегelmini.com www.gelmini-shop.it